

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/054711 A1

(51) International Patent Classification⁷: **F16G 11/14**,
A63B 29/02

(21) International Application Number:
PCT/AU2004/001685

(22) International Filing Date: 1 December 2004 (01.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003906657 1 December 2003 (01.12.2003) AU

(71) Applicant and

(72) Inventor: ANSTEE, Edward, David [AU/AU]; 11
Callantina Road, Hawthorn, Victoria 3122 (AU).

(74) Agents: PRYOR, Geoffrey, Charles et al.; Davies Col-
lison Cave, 1 Nicholson Street, Melbourne, Victoria 3000
(AU).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: LOCKABLE COUPLING HOOK



(57) Abstract: A coupling member (20) includes cylindrical body (22) and hook (24). Sleeve (70) slides over the outer surface of body (22) between an open position (as shown) and a closed position and carries pin (50) which is guided by slots (60,62) formed in body (22). Closure shaft (30) is mounted within body (22) and biased by spring (42) towards a closed position wherein end (32) of shaft (30) is received within recess (44) formed in portion (26) of hook (24). Pin (50) is slidably mounted in transverse bore (56) of shaft (30). Spring (58) biases pin head (52) towards shaft (30) so that when shaft (30) is in the closed position, pin head (52) is seated in recess (66) and shaft (30) is thereby locked in the closed position. Coupling member (20) can be used for securing lines in mountaineering or cave diving.